



## LIFT READER TABLEAU ACTIVATION

Transponder SmartCard reader for authorisation-dependent activation of lift panels.

### ADVANTAGES

- full integration into the authorization matrix of the Messerschmitt system
- securing access to guest, staff and administrative areas
- sturdy
- maintenance-free
- optics individually adjustable
- easy and quick installation

### FEATURES

- 13.56 Mhz radio frequency technology
- infrared interface for configuration
- logging of up to 415 door openings
- activatable BLE interface for the use of MobileKey features
- adjustable opening control according to locking plan
- optional: Transmission of presence detection to Messerschmitt system PC

### VERSIONS

- concealed arrangement (installation in elevator car wall)
- optional: Tiziano design

## Specifics

**Dimensions**

Structure height: 0mm  
Installation depth: 53 mm  
Dimensions: 80mm x 80mm

Other designs: upon request  
Power consumption

**Power consumption** 150 mA

**Weight** 150 g

**Protection class** IP 40

**temperature range** -25 °C - 50 °C

**Power Supply** 12 V DC

**Control** potential-free contact

**Connections** RS485 main bus  
RS485 component bus 12 V  
power supply

**Required cable** J-Y(St)Y 2 × 2 × 0.6 mm<sup>2</sup>

Errors and modifications reserved.